



连杆支承用滚针和保持架组件

Needle Roller and Cage Assemblies For Connecting Rod Bearing Arrangements

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		重量 Weight (Kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	Ew	Bc	动Cr Dynamic	静Cor Static	
8	KBK 8X11X10		8	11	10	3200	3100	0.00140
	KBK 8X11X12		8	11	12	3200	3100	0.00270
9	KBK9X12X11.6		9	12	11.6	4300	4600	0.0030
10	KBK 10X14X10	29242/10F	10	14	10	4400	4100	0.00420
	KBK 10X14X12.5		10	14	12.5	6500	6800	0.00577
	KBK 10X14X13	39242/10Y1	10	14	13	6000	6100	0.00590
	KBK 10X14X13/YB2		10	14	13	6500	6800	0.00580
	KBK 10X14X15	K101415Y	10	14	15	6500	6700	0.00580
11	KBK 11X15X12.5	K111512.5Y	11	15	12.5	6500	6900	0.00550
12	KBK12X15X15		12	15	15	7200	9900	0.0052
	KBK 12X15X16.6	K121516.6Y	12	15	16.6	6500	8600	0.00580
	KBK 12X16X13		12	16	13	6900	7700	0.00670
	KBK 12X16X13/YB2		12	16	13	6900	7700	0.00671
	KBK 12X16X16		12	16	16	8600	10200	0.00770
	KBK 12X16X17	K121617Y	12	16	17	8000	9400	0.00900
	KBK12X17X13		12	17	13	8300	8400	0.00604
	KBK 12X17X14		12	17	14	7600	7600	0.00950
	KBK12X17X14.2		12	17	14.2	9600	10200	0.00864
	KBK 12X17X14.5		12	17	14.5	9600	10200	0.00860
	KBK 12X17X15		12	17	15	9600	10200	0.00905
13	KBK 13X17X17.5		13	17	17.5	10300	13100	0.00860
14	KBK 14X18X14.7		14	18	14.7	7300	8500	0.00910
	KBK 14X18X17		14	18	17	7800	10500	0.00990
	KBK 14X18X20	K141820Y	14	18	20	9000	11200	0.01130
	KBK 14X19X17		14	19	17	11000	12600	0.01274
15	KBK 15X20X24	SZ-433	15	20	24	15500	20000	0.01860
16	KBK 16X20X20	K162020Y	16	20	20	11200	15500	0.01310
	KBK 16X20X24	SZ-444Y	16	20	24	12400	17500	0.01610
	KBK 16X21X18	K162118Y	16	21	18	12400	15100	0.01470

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		重量 Weight (Kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	Ew	Bc	动Cr Dynamic	静Cor Static	
18	KBK 18X22X22	K182222Y	18	22	22	14300	21900	0.01530
	KBK 18X23X23	K182323Y	18	23	23	15000	20000	0.02240

连杆支承用滚针和保持架组件

Needle Roller and Cage Assemblies For Connecting Rod Bearing Arrangements

轴径 Shaft Diameter	轴承代号		外形尺寸 Boundary			基本额定负荷		重量 Weight (Kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	Ew	Bc	动Cr Dynamic	静Cor Static	
8	KZK8X11X8.8		8	11	8.8	3150	3000	0.00173
10	KZK 10X13X8		10	13	8	3000	3000	0.0022
	KZK 10X14X8		10	14	8	3900	3400	0.0031
	KZK 10X14X10		10	14	10	4400	4100	0.0040
12	KZK12X16X10		12	16	10	6100	6600	0.003652
	KZK12X16X12		12	16	12	6200	7500	0.00515
14	KZK 14X18X13		14	18	13	7100	9400	0.0055
	KZK 14X19X12	K141912Y	14	19	12	8100	8500	0.0071
15	KZK 15X20X10		15	20	10	6900	7100	0.0068
16	KZK 16X22X12/YB2		16	22	12	9900	10100	0.0094
	KZK 16X22X12	19243/16Y	16	22	12	9900	10100	0.0094
	KZK16X22X12/YA		16	22	12	10500	11000	0.00976
	KZK 18X24X11.5		18	24	11.5	11100	12200	0.0105
	KZK18X24X12		18	24	12	11100	7900	0.0109
	KZK18X24X13.2		18	24	13.2	11100	12200	0.0119
	KZK 18X24X13.5		18	24	13.5	11100	12200	0.0119
	KZK 18X24X17	K182417Y	18	24	17	14200	16700	0.0151
19	KZK 19X25X16	K192516Y	19	25	16	14200	16700	0.0139
20	KZK 20X26X11.6	K202612Y	20	26	11.6	1100	12300	0.0108
	KZK20X26X14		20	26	14	12700	16600	0.015
	KZK 20X26X17	K202617Y	20	26	17	14100	16900	0.0159
	KZK 20X28X25	K202825Y	20	28	25	28100	34300	0.0336
	KZK 20X30X30	K203030Y	20	30	30	38000	44500	0.0531
22	KZK 22X28X15		22	28	15	14700	18300	0.0167
	KZK 22X28X16	K222816Y	22	28	16	15700	20000	0.0182
	KZK 22X30X18		22	30	18	21900	25500	0.02814
23	KZK 23X30X14		23	30	14	17200	20600	0.0202
23.1	KZK 23.1X28.1X14		23.1	28.1	14	13100	18400	0.0129
23.3	KZK 23.3X32.3X17	SZ-443Y	23.3	32.3	17	23600	26400	0.0186
24	KZK 24X30X16	K243016Y	24	30	16	17200	23000	0.0182
	KZK 24X30X17	K24X30X17Y	24	30	17	18300	24900	0.0205
25	KZK 25X30X13		25	30	13	12500	17600	0.0138
	KZK 25X31X20	K253120Y	25	31	20	21200	30700	0.0219
25.1	KZK 25.1X30.1X13.9		25.1	30.1	13.9	14100	20600	0.0148
26	KZK26X31X13.8		26	31	13.8	12900	20700	0.01533
	KZK26X31X14		26	31	14	12900	20700	0.0167
	KZK26X31X16		26	31	16	15800	23900	0.01819
	KZK 26X32X15		26	32	15	15800	21300	0.0194
27	KZK27X36X21		27	36	21	30700	38700	0.045282
28	KZK 28X33X14F1C1		28	33	14	14800	22800	0.0163
	KZK 28X34X17		28	34	17	21900	33300	0.0225
	KZK28X35X17F1C1		28	35	17	20700	30900	0.03064
	KZK 28X36X16		28	36	16	23800	30300	0.0323

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		重量 Weight (Kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	Ew	Bc	动Cr Dynamic	静Cor Static	
	KZK 28X36X17		28	36	17	26500	34800	0.0348
29	KZK29X37X16		29	37	16	23700	30400	0.036924
	KZK30X37X20		30	37	20	23800	38100	0.037
30	KZK 30X38X16		30	38	16	24600	32400	0.0344
	KZK 30X38X18		30	38	18	27700	37700	0.0388
32	KZK 32X41X18		32	41	18	33000	44600	0.0476