



双列滚针轴承

Needle Roller Bearings , Double Row

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原来代号 Original Designation	Fw、d	D	B、C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
有内圈双列滚针轴承										
10	NA6900A	6534900	10	22	22	8800	11200	14400	21600	0.03800
12	NA6901		12	24	22	9100	12200	13500	20700	0.04790
15	NA6902A	6534902	15	28	23	10900	16600	12000	18000	0.06600
	NA6902A/P6	E6534902	15	28	23	10900	16600	12000	18000	0.06600
17	NA6903A	6534903	17	30	23	10400	9400	10000	16000	0.07165
	NA6903A/P6	E6534903	17	30	23	11100	17600	10000	16000	0.07170
20	NA6904A	6534904	20	37	30	22500	38400	9600	14400	0.10000
	NA6904		20	37	30	35200	48500	9600	14400	0.14100
21.8	KI21.8X31.8X33.5		21.8	31.8	33.5	41500	39800	6660	14400	0.06980
25	NA6905A	6534905	25	42	30	24600	40300	8500	12400	0.16100
30	NA6906A	6534906	30	47	30	24100	47100	7300	10800	0.19200
35	NA6907A	6534907	35	55	36	36400	74500	6100	9100	0.31000
45	NA6909A	6534909	45	68	40	54900	110400	4900	7300	0.49500
50	NA6910A	6534910	50	72	40	57900	124100	4400	6600	0.51500
55	NA6911A	6534911	55	80	45	65200	148900	4100	6000	0.78000
60	NA6912A	6534912	60	85	45	70000	164500	3800	5600	0.80800
65	NA6913A	6534913	65	90	45	71800	175000	3500	5300	0.83300
70	NA6914A	6534914	70	100	54	89700	242000	3200	4800	1.34000
75	NA6915A	6534915	75	105	54	83100	256800	3000	4500	1.45000
80	NA6916		80	110	54	85000	234900	3200	4800	1.63200
90	NA6918		90	125	63	159000	416000	2300	3500	2.31000
95	NA6919A	6534919	95	130	63	127000	408200	2300	3500	2.50000
无内圈双列滚针轴承										
12	RNA0122425ZW	SZ-427	12	24	25	11900	14000	15300	23200	0.03780
14.73	RNA14.73X26.7X27.5A/YA	SZ-482	14.73	26.7	27.5	10400	16000	14000	21000	0.07300
16	RNA6901A	6634901	16	24	22	9100	12200	13500	20700	0.03100
20	RNA6002A	6634102	20	32	30	23900	34500	12000	18000	0.04300
	RNA6902A	6634902	20	28	23	10200	17200	12000	18000	0.04000

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)			基本额定负荷 Basic Load Rating (N)		极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原来代号 Original Designation	Fw、d	D	B、C	动Cr Dynamic	静Cor Static	脂润滑 Grease	油润滑 Oil	
22	RNA223030AZW	634704	22	30	30	14200	27100	10000	16000	0.05100
	RNA22X40X36A/P6		22	40	36	29400	36600	9600	16000	0.20604
	RNA224036AZW	SZ-473	22	40	36	23700	45000	10000	16000	0.21700
24	RNA0V243732ZW	984905	24	37	32	42400	88100	10000	15000	0.14140
25	RNA6904A	6634904	25	37	30	24400	37600	9600	14400	0.10000
28	RNA283833AZWS	SZ-446	28	38	33	20800	40700	9100	13600	0.10000
	RNA283833AZW	SZ-446P	28	38	33	20800	40700	9100	13600	0.10000
30	RNA6905		30	42	30	24600	40300	8500	12400	0.11930
	RNA6905A	6634905	30	42	30	24600	40300	8500	13000	0.11200
30	RNA0303736ZW	SZ-408	30	37	36	25200	62800	8500	13000	0.07900
35	RNA6906		35	47	30	24100	47100	7300	10800	0.12600
	RNA6906A	6634906	35	47	30	24100	47100	7300	10800	0.12600
40	RNA69/32A	66349/32	40	52	36	27500	59000	6400	9500	0.16200
42	RNA6907A	6634907	42	55	36	36400	74500	6100	9100	0.19300
52	RNA6909A	6634909	52	68	40	54900	110400	4900	7300	0.33800
58	RNA6910A	6634910	58	72	40	57900	124100	4400	6600	0.31000
63	RNA6911A	6634911	63	80	45	65200	148900	4000	6000	0.47000
65	RNAVP658045	684713	65	80	45	87300	275900	4000	5900	0.73110
68	RNA6912A	6634912	68	85	45	70000	164500	3800	5600	0.48800
80	RNA6914A	6634914	80	100	54	89700	242000	3200	4800	0.85700
100	RNA6917A	6634917	100	120	63	120600	367800	2600	3800	1.20000
110	RNA6919A	6634919	110	130	63	138300	403000	2300	3500	1.46000